

Multipurpose

High

High shoes



HRO



The +

- *Lightness.
- *Water-repellent.
- *Comfort of use (insole HI-POLY foam + midsole EVA).
- *Urban style.

PURCHASE PACKAGING

Référence	Taille	Carton
9SHU150037	37	6
9SHU150038	38	6
9SHU150039	39	6
9SHU150040	40	6
9SHU150041	41	6
9SHU150042	42	6
9SHU150043	43	6
9SHU150044	44	6
9SHU150045	45	6
9SHU150046	46	6
9SHU150047	47	6

DESCRIPTION

Trendy and timeless, SHUNGITE is a light and comfortable ESD shoe. Metal-free, SHUNGITE offers the wearer lightness, flexibility and resistance in wet conditions thanks to its water-repellent nubuck upper. The emphasis is on comfort: composite toe cap, textile anti-perforation midsole and Hi-Poly foam insole with cushions. The nitrile rubber outsole, non-slip on metal and steel floors, is also resistant to hydrocarbons and heat.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Anthracite
Upper	Water-repellent / Nubuck leather
Toecap	Composite
Puncture resistant sole	Textile
Midsole	EVA
Outsole	Rubber nitrile
Insole	HI-POLY foam
Closing	Lacing closure
Lining	Breathable 3D mesh

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)



EN ISO 20345:2011

S3

SRC

HRO

ESD

EPI CAT. I

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Heat contact resistant outsole (60 seconds at 300°C)

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

RETAILER STAMP