

Ref. 6PHW400

Vented Helmet General Use



The +

PERFORMANCE

- High resistance level (lateral deformation (LD), low temperature - 30°C)

- ABS Shell

COMFORT

- Side ventings
- Integrated safety glasses
- Good fitting and lightweight feeling (head balance)

- Easy adjustment by ratchet
- Wide field of vision thanks to the short peak

- 3D textile sweatband

LIGHTWEIGHT

- 450g

Compatible with badge holder (6POBA) and earcups (6MX3000NSI)

DESCRIPTION

PHOENIX WIND Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, side ventings, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 point chinstrap as a standard

SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Regional/public authorities

Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHW400NSI	-		16

SALES PACKAGING



Individual pack

See also

VARIANTS

TECHNICAL FEATURES

Color	HV Yellow
Color 2	Black
Shell material	ABS
Adjustment	Adjustment by ratchet from 52 to 63 cm
Weight	450g
Service life	Manufacturing date indicated under the peak Shelf life: Storage for 2 years in standard conditions Use for 5 years in good conditions
Main risk	Prevention from falling objects and head injuries or head trauma
Features	ABS Shell LDPE 6 points harness Size adjustment from 52 to 63 cm
Harness features	6 points harness made of polyethelene 6 textile webbings
Vented	Side ventings

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2314

Delivered by CSI (0497) Cascina Traversagna- 2120030 Senago (MI) Italy



EPI CAT. II

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN397:2012 + A1:2012

Industrial safety helmets

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

RETAILER STAMP

MAJ 13/01/2023